

LOW PRESSURE GAUGES
UL CERTIFIED
UL NUMBER: CU-2581-LG (60 PSI) - Art. 23/10/97 - L1
UL NUMBER: CU-2581-GR (115 PSI) - Art. 23/10/98 - L2
UL NUMBER: CU-2581-GZ (160 PSI) - Art. 23/10/99 - L3

SAFETY VALVE CALIBRATION:
FROM 30 TO 160 PSI

SEE ATTACHMENT
FOR GASKET MATERIAL

CO2 USA CYLINDER CONNECTION
CGA-V1 N°320
Art. 24/510/3
Art. 20/10/79
Art. 24/510/4

BODY KIT ALREADY
UL CERTIFIED
YKFT-SA44354

GAUGES OPTIONS

OUTLET OPTIONS

HIGH PRESSURE GAUGES
UL CERTIFIED
UL NUMBER: BU-2581-CR (2000 PSI) - Art. 23/10/100 - H1
UL NUMBER: BU-2581-AL (3000 PSI) - Art. 23/10/101 - H2

"Y" OUTLET FITTING - ONLY FOR FIRST OR SECOND BODY
Art. 24/510/28
NOT FOR BOTH
(DIMENSIONAL PROBLEMS)

- U1. BALL VALVE 1/4" NPT - Art. 20/147
- U2. BALL VALVE WITH BARB Ø 5/16 - Art. 20/846
- U3. BALL VALVE WITH J.GUEST Ø 3/8 - Art. 20/843
- U4. BALL VALVE WITH J.GUEST Ø 5/16 - Art. 20/844
- U5. BALL VALVE WITH 7/16"-20UNF NON RETURN VALVE - Art. 20/845
- U6. J.GUEST Ø 3/8 - Art. PI011222S
- U7. J.GUEST Ø 5/16 - Art. PM010822S
- U8. 7/16"-20UNF NON RETURN VALVE - Art. 24/510/17
- U9. BARB Ø 5/16 - Art. 20/846/1
- U10. BALL VALVE WITH BARB Ø 3/8 - Art. 20/851
- U11. BARB Ø 3/8 - Art. 24/510/25